NSN 4820-00-457-0256



Stop-check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-457-0256 **Thread Class:** 2b 2nd end **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Connection Style:** Flare (tube) 2nd end **Valve Operation Method:** Manual **Connection Type:** Threaded internal tube 2nd end **Mounting Facility: Bracket Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 2nd end Material: Aluminum alloy flow control device and aluminum flow control device Media For Which Designed: Oil, hydraulic 2nd response **Style Designator:** Angle **Test Data Document:** 81349-mil-v-5528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:**

--

N/a

Unf all ends
Shelf Life:

Unit Of Measure:

NSN 4820-00-457-0256

Stop-check Valve - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A530b0