NSN 4820-00-457-0707

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-457-0707 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends Seat Angle: 37.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, alloy 2024 federal specification single material response Media For Which Designed: Air single response **Surface Treatment:** Oxide film **Surface Treatment Specification:** Mil-c-5541 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

NSN 4820-00-457-0707

Check Valve - Page 2 of 2



N/a	
Unit Of	Measure:

Shelf Life:

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-c-5541 spec.