

<b>NSN 4820-00-457-0707</b> Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-457-0707
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, alloy 2024 federal specification single material response
Media For Which Designed:
Air single response
Surface Treatment:
Oxide film
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

## NSN 4820-00-457-0707

Check Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

## Mil-std (military Standard):

Mil-c-5541 spec.

