NSN 4820-00-460-2212

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-460-2212

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
85.0 pounds per hour
Maximum Operating Temp:
180.0 degrees fahrenheit single response
End Application:
Grumman aerospace a10 aircraft
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+300.0/+1500.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
1350.0 pounds per square inch
Material:
Steel comp 303
Material Specification:
66 federal standard single material response
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end

NSN 4820-00-460-2212

Safety Relief Valve - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0