

View Online at <https://aerobasegroup.com/nsn/4820-00-460-6797>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.5 gallons per minute

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Features Provided:

Pressure tight outlet side

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Seat Angle:

37.0 degrees all ends

Opening Pressure Setting:

210.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches all ends

Material:

Steel comp 416 stem

Material Specification:

Sae ca360 assn standard single material response body

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.