## NSN 4820-00-461-1548

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-461-1548

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Mounting Facility:
Bulkhead
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 1st end
Maximum Operating Pressure:
600.0 pounds per square inch single response
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.625 inches 1st end
Special Features:
Bulkhead type threads on second end
Material:
Rubber synthetic packing
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end

## NSN 4820-00-461-1548

Restrictor Check Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0

