# NSN 4820-00-463-2029

Stop-check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-463-2029



#### Pipe Size Accommodated:

0.750 inches all ends

#### **Flow Control Device:**

Disk

#### Bonnet Type:

Outside screw-yoke

#### **Bonnet Attachment Method:**

Bolted

#### Maximum Operating Temp:

975.0 degrees fahrenheit single response

#### **Connection Style:**

Socket (pipe) all ends

#### Valve Operation Method:

Manual

#### **Connection Type:**

Unthreaded internal pipe all ends

#### **Mounting Position:**

Horizontal

#### **Features Provided:**

Bonnet packing

#### Maximum Operating Pressure:

600.0 pounds per square inch single response

#### **Special Features:**

Valve size 3/4 in.

#### Material:

Steel seat

#### **Material Specification:**

Mil-r-17131, mil-rcocr-a military specification single material response seat

#### Media For Which Designed:

Steam single response

#### Style Designator:

Straight thru

### Test Data Document:

81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A530b0

## NSN 4820-00-463-2029

Stop-check Valve - Page 2 of 2

### Mil-std (military Standard):

Mil-r-17131 spec.

