NSN 4820-00-463-2156

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-463-2156

view Offiline at https://aerobasegroup.com/hist//4020-00-403-2100
Pipe Size Accommodated:
1.000 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
975.0 degrees fahrenheit single response
Connection Style:
Socket (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Special Features:
Valve size 1 in.
Material:
Steel seat
Material Specification:
Mil-r-17131, mil-rcocr-a military specification single material response flow control device
Media For Which Designed:
Steam single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
B composition
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 4820-00-463-2156

Stop-check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-r-17131 spec.