NSN 4820-00-463-2437

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-463-2437 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Connection Style:** G46a plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 125.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response Media For Which Designed: Nitrogen, gaseous 3rd response **Surface Treatment:** Anodize **Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4820-00-463-2437

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0