## NSN 4820-00-467-2583

Check Valve - Page 1 of 2

**Pipe Size Accommodated:** 

Straight thru



View Online at https://aerobasegroup.com/nsn/4820-00-467-2583

0.125 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Plain, optional end (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
27 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-200/3, alloy 2024, t3511 federal specification single material response
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:

## NSN 4820-00-467-2583

Check Valve - Page 2 of 2



Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
<b>Demilitarization:</b> No

Mil-std (military Standard):

Mil-a-8625 spec.