## NSN 4820-00-469-7673

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-469-7673

Pipe Size Accommodated:						
0.500 inches 2nd end						
Thread Direction:						
Right-hand 1st end						
Flow Control Device:						
Disk						
Bonnet Type:						
Inside spring						
Bonnet Attachment Method:						
Threaded						
Disk Loading Method:						
Spring						
Maximum Operating Temp:						
406.0 degrees fahrenheit 2nd response						
Connection Style:						
Plain, optional en (pipe) 1st end						
Valve Operation Method:						
Automatic						
Connection Type:						
Threaded internal pipe 1st end						
Features Provided:						
Bonnet packing and pressure tight outlet side						
Thready Qty Per Inch (tpi):						
14 2nd end						
Maximum Operating Pressure:						
250.0 pounds per square inch 1st response						
Thread Size:						
0.500 inches 2nd end						
Opening Pressure Setting:						
15.0 pounds per square inch						
Material:						
Steel stem						
Material Specification:						
Qq-c-390, alloy b5 federal specification single material response body						
Media For Which Designed:						
Alcohol, methyl 2nd response						
Style Designator:						
Angle						
Thread Series Designator:						
Npt 1st end						
Shelf Life:						
N/a						

## NSN 4820-00-469-7673

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0