NSN 4820-00-469-7679

Globe Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-469-7679

Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Valve Size:
3.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
7.500 inches 1st end
Face To Face Distance:
9.500 inches
Thickness:
0.625 inches 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
5.000 inches 1st end
Material:
Stainless steel stem
Material Specification:
66 federal standard single material response body and aisi/sae 8622h assn standard single material response body

NSN 4820-00-469-7679

Globe Valve - Page 2 of 2



Me	dia	For	Which	Design	ied:

Steam single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0