

View Online at <https://aerobasegroup.com/nsn/4820-00-469-7681>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

9.000 inches 1st end

Face To Face Distance:

11.500 inches

Thickness:

0.625 inches 1st end

Bolt Hole Diameter:

0.750 inches 1st end

Bolt Circle Diameter:

7.500 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

6.188 inches 1st end

Material:

Stainless steel stem

Material Specification:

66 federal standard single material response body and aisi/sae 8622h assn standard single material response body

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0