NSN 4820-00-470-0509



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-470-0509 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response Thread Size: 1.312 inches all ends Seat Angle: 37.0 degrees 1st end Material: Steel comp 304 flow control device and steel comp 303 flow control device and rubber butadiene-acrylonitrile class nbr flow control device **Material Specification:** Fed standard 66, aisi 304/sae 30304 federal standard 1st material response flow control device and federal standard 66, aisi 303/sae 30303 federal standard 2nd material response flow control device Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Style Designator:** Straight thru

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-00-470-0509

Check Valve - Page 2 of 2



Fiig:

A530b0