NSN 4820-00-470-1732

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-470-1732

| Pipe Size Accommodated: |
|---|
| 0.750 inches all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 60.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe all ends |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches all ends |
| Opening Pressure Setting: |
| 3200.0 pounds per square inch |
| Material: |
| Steel stem |
| Media For Which Designed: |
| Gas, natural 2nd response |
| Surface Treatment: |
| Copper |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4820-00-470-1732

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0