NSN 4820-00-472-2399

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-472-2399

| View Online at https://aerobasegroup.com/nsn/4820-00-472-2399 |
|--|
| Pipe Size Accommodated: |
| 2.500 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Renewable Seat Ring Type: |
| Welded |
| Maximum Operating Temp: |
| 500.0 degrees fahrenheit single response |
| Connection Style: |
| Beveled (pipe) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe all ends |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Special Features: |
| Stop valve type; one piece bonnet |
| Material: |
| Steel seat |
| Material Specification: |
| Mil-r-17131 military specification single material response seat |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Straight thru |
| Test Data Document: |
| 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-v-22052 government specification |
| Specification Or Standard: |
| D composition |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 4820-00-472-2399

Globe Valve - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-17131 spec.