NSN 4820-00-472-2399

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-472-2399

View Online at https://aerobasegroup.com/nsn/4820-00-472-2399
Pipe Size Accommodated:
2.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Welded
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Connection Style:
Beveled (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Butt weld pipe all ends
Features Provided:
Bonnet packing
Maximum Operating Pressure:
150.0 pounds per square inch single response
Special Features:
Stop valve type; one piece bonnet
Material:
Steel seat
Material Specification:
Mil-r-17131 military specification single material response seat
Media For Which Designed:
Steam single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-v-22052 government specification
Specification Or Standard:
D composition
Shelf Life:
N/a

--

Unit Of Measure:

NSN 4820-00-472-2399

Globe Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-17131 spec.