## NSN 4820-00-472-4072

Stop-check Valve - Page 1 of 2

A530b0



View Online at https://aerobasegroup.com/nsn/4820-00-472-4072

View Online at https://aerobasegroup.com/nsn/4820-00-472-4072
Pipe Size Accommodated:
1.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Connection Style:
Socket (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Features Provided:
Bonnet packing
Maximum Operating Pressure:
600.0 pounds per square inch single response
Special Features:
Valve size 1.500 in.
Material:
Steel seat
Material Specification:
Astm a105, grade 2 assn standard 1st material response seat and mil-r-17131, mil-rcocr-a military specification 2nd material response seat
Media For Which Designed:
Steam single response
Style Designator:
Angle
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

## NSN 4820-00-472-4072

Stop-check Valve - Page 2 of 2



Mil-std (military Standard):

Mil-r-17131 spec.