

View Online at <https://aerobasegroup.com/nsn/4820-00-473-4225>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

6 2nd end

**Connection Style:**

Socket (tube) err-100

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes 2nd end

**Connection Type:**

Unthreaded internal tube 1st end

**Features Provided:**

Bonnet packing

**Valve Size:**

2.000 inches

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Outside Diameter:**

5.563 inches 2nd end

**Thickness:**

0.437 inches 2nd end

**First Connection Face To Centerline Distance:**

5.875 inches

**Bolt Hole Diameter:**

0.563 inches 2nd end

**Second Connection Face To Centerline Distance:**

4.500 inches

**Bolt Circle Diameter:**

4.438 inches 2nd end

**Flange Face Design:**

Plain 2nd end

**Outside Diameter Tube Accommodated:**

2.375 inches 1st end

**Extra Long Reference Number:**

490363alt12pcct0gjnbn2a3t0k3t3t0v3

**Material:**

Nickel alloy stem

**Style Designator:**

Angle flanged ends

**Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0