

View Online at <https://aerobasegroup.com/nsn/4820-00-473-4225>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

6 2nd end

Connection Style:

Socket (tube) err-100

Valve Operation Method:

Manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Unthreaded internal tube 1st end

Features Provided:

Bonnet packing

Valve Size:

2.000 inches

Maximum Operating Pressure:

200.0 pounds per square inch single response

Outside Diameter:

5.563 inches 2nd end

Thickness:

0.437 inches 2nd end

First Connection Face To Centerline Distance:

5.875 inches

Bolt Hole Diameter:

0.563 inches 2nd end

Second Connection Face To Centerline Distance:

4.500 inches

Bolt Circle Diameter:

4.438 inches 2nd end

Flange Face Design:

Plain 2nd end

Outside Diameter Tube Accommodated:

2.375 inches 1st end

Extra Long Reference Number:

490363alt12pcct0gjn2a3t0k3t3t0v3

Material:

Nickel alloy stem

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0