## NSN 4820-00-474-1749

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-474-1749 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal boss all ends **Mounting Facility:** Threaded fastener **Mounting Position:** Horizontal or vertical **Features Provided:** Valve stem lock shield **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Outside Diameter Tube Accommodated:** 0.500 inches 1st end **Special Features:** Handle turns cw 90 degrees for open position Material: Steel stem **Surface Treatment:** Anodize **Style Designator:** Straight thru

Supplementary Features:

Optional flow control device: stem

## NSN 4820-00-474-1749

Lift-check Valve - Page 2 of 2



Thread	Series	Desi	ignat	or:

Unf all ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0