NSN 4820-00-474-1749

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-474-1749

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

Gasket seal (boss) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal boss all ends

Mounting Facility:

Threaded fastener

Mounting Position:

Horizontal or vertical

Features Provided:

Valve stem lock shield

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

Handle turns cw 90 degrees for open position

Material:

Steel stem

Surface Treatment:

Anodize

Style Designator:

Straight thru

Supplementary Features:

Optional flow control device: stem

NSN 4820-00-474-1749

Lift-check Valve - Page 2 of 2

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

