## NSN 4820-00-474-1759

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-474-1759

| 0.125 inches 2nd end                     |
|--|
| Thread Class:                            |
| 3a 1st end                               |
| Thread Direction:                        |
| Right-hand 1st end                       |
| Flow Control Device:                     |
| Poppet                                   |
| Bonnet Type:                             |
| Packing retaining                        |
| Disk Loading Method:                     |
| Spring                                   |
| Maximum Operating Temp:                  |
| 160.0 degrees fahrenheit single response |
| Connection Style:                        |
| Plain (pipe) 2nd end                     |
| Valve Operation Method:                  |
| Automatic                                |
| Connection Type:                         |
| Threaded external tube 1st end           |
| Features Provided:                       |
| Pressure tight outlet side               |
| Thready Qty Per Inch (tpi):              |
| 27 2nd end                               |
| Thread Size:                             |
| 0.437 inches 1st end                     |
| Seat Angle:                              |
| 37.0 degrees 1st end                     |
| Opening Pressure Setting:                |
| 25.0 pounds per square inch              |
| Outside Diameter Tube Accommodated:      |
| 0.250 inches 1st end                     |
| Material:                                |
| Stainless steel seat                     |
| Style Designator:                        |
| Straight thru                            |
| Thread Series Designator:                |
| Unf 1st end                              |
| Shelf Life:                              |
| N/a                                      |
|  |

--

## NSN 4820-00-474-1759

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0