

View Online at <https://aerobasegroup.com/nsn/4820-00-474-2252>

**Body Material:**

Aluminum alloy

**Outside Surface Treatment:**

Any acceptable

**Body Style:**

Tee angle

**Furnished Items:**

Automatic relief valve

**Media For Which Designed:**

Fluid, petroleum base

**First End Connection Type:**

Threaded internal tube

**First End Outside Diameter Tube Accommodated:**

0.500 inches

**First End Thread Size And Series/type Designator:**

3/4-16 unf

**First End Thread Class:**

2b

**First End Thread Direction:**

Right-hand

**Second End Relationship With First End:**

Identical

**Third End Relationship With Preceding Ends:**

Not identical with first or second end

**Third End Connection Type:**

Threaded internal tube

**Third End Outside Diameter Tube Accommodated:**

0.250 inches

**Third End Thread Size And Series/type Designator:**

7/16-20 unf

**Third End Thread Class:**

2b

**Third End Thread Direction:**

Right-hand

**Seat Material:**

Steel, corrosion resisting

**Flow Control Device:**

Cone, top guided

**Flow Control Device Material:**

Steel, corrosion resisting

**End Connection Quantity:**

3

**Outlet Pressure Range:**

+800.0 to 1050.0 pounds per square inch

**Regulation Type:**

Automatic double stage

**Valve Stem Design:**

Double seat

**Valve Loading Method:**

Spring

**Remote Actuation Method:**

Spool

**Maximum Inlet Pressure Rating:**

800.0 pounds per square inch

**Outlet Pressure Accuracy Rating:**

Not rated

**Filter:**

Not included

**Special Features:**

10 gpm maximum flow capacity at maximum rated inlet and outlet pressures

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A21100