

View Online at <https://aerobasegroup.com/nsn/4820-00-474-2252>

Body Material:

Aluminum alloy

Outside Surface Treatment:

Any acceptable

Body Style:

Tee angle

Furnished Items:

Automatic relief valve

Media For Which Designed:

Fluid, petroleum base

First End Connection Type:

Threaded internal tube

First End Outside Diameter Tube Accommodated:

0.500 inches

First End Thread Size And Series/type Designator:

3/4-16 unf

First End Thread Class:

2b

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Third End Relationship With Preceding Ends:

Not identical with first or second end

Third End Connection Type:

Threaded internal tube

Third End Outside Diameter Tube Accommodated:

0.250 inches

Third End Thread Size And Series/type Designator:

7/16-20 unf

Third End Thread Class:

2b

Third End Thread Direction:

Right-hand

Seat Material:

Steel, corrosion resisting

Flow Control Device:

Cone, top guided

Flow Control Device Material:

Steel, corrosion resisting

End Connection Quantity:

3

Outlet Pressure Range:

+800.0 to 1050.0 pounds per square inch

Regulation Type:

Automatic double stage

Valve Stem Design:

Double seat

Valve Loading Method:

Spring

Remote Actuation Method:

Spool

Maximum Inlet Pressure Rating:

800.0 pounds per square inch

Outlet Pressure Accuracy Rating:

Not rated

Filter:

Not included

Special Features:

10 gpm maximum flow capacity at maximum rated inlet and outlet pressures

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100