NSN 4820-00-475-3642

Safety Relief Valve - Page 1 of 2

Thread Class: 3b all ends

Piston

Bonnet Type:

Thread Direction:
Right-hand all ends
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-475-3642

Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+250.0/+3000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
1.062 inches all ends
Seat Angle:
45.0 degrees all ends
Opening Pressure Setting:
1500.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.750 inches all ends
Material:
Steel flow control device
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Err-090

NSN 4820-00-475-3642

Safety Relief Valve - Page 2 of 2



Thread Series Designator:
Unj all ends
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0