

View Online at <https://aerobasegroup.com/nsn/4820-00-476-9739>

Pipe Size Accommodated:

0.500 inches 2nd end

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Connection Style:

Plain, optional en (pipe) 2nd end

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal tube 1st end

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

14 2nd end

Maximum Operating Pressure:

100.0 pounds per square inch single response

Thread Size:

0.500 inches 2nd end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Special Features:

Washer furn rubber, friction ring brass.1 escutcheon plate, 1 slipnut, a chromium plated nipple 1/2 in. lps 4 in. Lg, and 1 flexible chromium plated 3/8 in. Od 15 in. Lg min. Furnished

Material:

Plastic flow control device

Surface Treatment:

Chromium

Style Designator:

Angle

Thread Series Designator:

Npt 2nd end

Furnished Items And Quantity:

1 friction ring and 1 washer

Specification Or Standard:

6a type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0