NSN 4820-00-477-1809

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-477-1809 **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Renewable Seat Ring Type:** Threaded **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Valve stem lock shield **Adjustable Pressure Range:** +65.0/+180.0 pounds per square inch **Maximum Operating Pressure:** 180.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Opening Pressure Setting:** 65.0 pounds per square inch Material: Stainless steel stem **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Angle **Thread Series Designator:** Npt all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-477-1809

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.