Ν



NSN 4820-00-479-2695 Safety Relief Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-479-2695
Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+50.0/+90.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
80.3 pounds per square inch
Material:
Aluminum alloy 2024 body
Media For Which Designed:
Oil, hydraulic single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Nptf 1st end

Shelf Life:

N/a

NSN 4820-00-479-2695

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.

