NSN 4820-00-479-2695

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-479-2695

Pipe Size Accommodated:				
0.250 inches 1st end				
Thread Direction:				
Right-hand 1st end				
Flow Control Device:				
Poppet				
Bonnet Type:				
Inside spring				
Bonnet Attachment Method:				
Threaded				
Disk Loading Method:				
Spring				
Connection Style:				
Plain, optional en (pipe) 1st end				
Valve Operation Method:				
Automatic				
Connection Type:				
Threaded internal pipe 1st end				
Thready Qty Per Inch (tpi):				
18 1st end				
Adjustable Pressure Range:				
+50.0/+90.0 pounds per square inch				
Maximum Operating Pressure:				
3000.0 pounds per square inch single response				
Thread Size:				
0.250 inches 1st end				
Opening Pressure Setting:				
80.3 pounds per square inch				
Material:				
Aluminum alloy 2024 body				
Media For Which Designed:				
Oil, hydraulic single response				
Surface Treatment:				
Anodize				
Surface Treatment Specification:				
Mil-a-8625, type 1 military specification single treatment response				
Style Designator:				
Straight thru				
Thread Series Designator:				
Nptf 1st end				
Shelf Life:				
N/a				

NSN 4820-00-479-2695

Safety Relief Valve - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.