## NSN 4820-00-480-7432

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-480-7432

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Opening Pressure Setting:
20.0 pounds per square inch
Special Features:
Inline type
Material:
Copper alloy and rubber butadiene-acrylonitrile class nbr flow control device
Material Specification:
Sae ca 360 assn standard single material response seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

## NSN 4820-00-480-7432

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0