NSN 4820-00-481-2382

Check Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-00-481-2382

3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
16 1st end
Maximum Operating Pressure:
5000.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Seat Angle:
37.0 degrees all ends
Outside Diameter Tube Accommodated:
0.500 inches all ends
Material:
Stainless steel flow control device
Material Specification:
Fed standard 66, aisi 303/sae 30303 federal standard single material response seat
Media For Which Designed:
Oil, hydraulic single response
Surface Treatment:
Passivate
Style Designator:
Straight thru
Thread Series Designator:
Unf all ends
Shelf Life:
N/a

NSN 4820-00-481-2382

Check Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A530b0