## NSN 4820-00-481-6686

Check Valve - Page 1 of 2

Pipe Size Accommodated:

0.250 inches 2nd end

Thread Class: 3a 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-481-6686

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Special Features:
Cracking pressure 1.0 psi
Material:
Steel comp 316 flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

## NSN 4820-00-481-6686

Check Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A530b0