

View Online at <https://aerobasegroup.com/nsn/4820-00-482-2420>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

400.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

6.000 inches

Maximum Operating Pressure:

200.0 pounds per square inch 2nd response

Outside Diameter:

11.000 inches all ends

Thickness:

1.000 inches all ends

First Connection Face To Centerline Distance:

7.000 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

7.000 inches

Bolt Circle Diameter:

9.500 inches all ends

Flange Face Design:

Plain 1st end

Special Features:

Valve size 6.000 in.

Material:

Steel stem

Material Specification:

Astma126-61t, classb assn standard single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0