

View Online at <https://aerobasegroup.com/nsn/4820-00-482-2420>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

400.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

6.000 inches

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Outside Diameter:**

11.000 inches all ends

**Thickness:**

1.000 inches all ends

**First Connection Face To Centerline Distance:**

7.000 inches

**Bolt Hole Diameter:**

0.875 inches all ends

**Second Connection Face To Centerline Distance:**

7.000 inches

**Bolt Circle Diameter:**

9.500 inches all ends

**Flange Face Design:**

Plain 1st end

**Special Features:**

Valve size 6.000 in.

**Material:**

Steel stem

**Material Specification:**

Astma126-61t, classb assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Angle flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0