## NSN 4820-00-482-4028

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-482-4028 **Pipe Size Accommodated:** 0.500 inches all ends Flow Control Device: Disk **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method: Bolted Maximum Operating Temp:** 975.0 degrees fahrenheit single response **Connection Style:** Socket (pipe) all ends **Valve Operation Method:** Manual **Connection Type:** Unthreaded internal pipe all ends **Mounting Position:** Horizontal **Features Provided:** Bonnet packing **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Special Features:** Valve size 1/2 in. Material: Steel stem **Material Specification:** Mil-r-17131, mil-rcocr-a military specification single material response seat Media For Which Designed: Steam single response **Style Designator:** Straight thru **Test Data Document:** 81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Or Standard:** B composition Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 4820-00-482-4028

Stop-check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-r-1713 spec.