

View Online at <https://aerobasegroup.com/nsn/4820-00-482-4555>

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

Plain, optional end (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Material:

Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device or steel comp 303 flow control device and rubber butadiene-acrylonitrile class nbr flow control device

Material Specification:

Qq-s-763, class 304 federal specification 1st material response flow control device and mil-p-5315 military specification 2nd material response flow control device or qq-s-764, type 303-canceled federal specification 3rd material response flow control device and mil-p-5315 military specification 4th material response flow control device

Media For Which Designed:

Hydraulic fluid, petroleum base 2nd response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-5315 spec.