

View Online at <https://aerobasegroup.com/nsn/4820-00-482-4555>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

180.0 degrees fahrenheit single response

**Connection Style:**

Plain, optional end (pipe) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded internal pipe all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.125 inches all ends

**Material:**

Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device or steel comp 303 flow control device and rubber butadiene-acrylonitrile class nbr flow control device

**Material Specification:**

Qq-s-763, class 304 federal specification 1st material response flow control device and mil-p-5315 military specification 2nd material response flow control device or qq-s-764, type 303-canceled federal specification 3rd material response flow control device and mil-p-5315 military specification 4th material response flow control device

**Media For Which Designed:**

Hydraulic fluid, petroleum base 2nd response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0

**Mil-std (military Standard):**

Mil-p-5315 spec.