

View Online at <https://aerobasegroup.com/nsn/4820-00-483-0695>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external pipe all ends

Features Provided:

Bonnet packing

Valve Size:

0.500 inches

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Special Features:

Pre-inserted silver solder ring union ends

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Supplementary Features:

7this item has been reviewed for asbestos material; the current approved sources, 76364 and 80064 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Test Data Document:

03950-acid 882057031 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A046b0