

View Online at <https://aerobasegroup.com/nsn/4820-00-483-0696>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Material:

Plastic polyamide flow control device

Material Specification:

Qq-n-286 federal specification 1st material response stem or 164-61 assn standard 2nd material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Test Data Document:

03950-acid 882057032 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0