

View Online at <https://aerobasegroup.com/nsn/4820-00-483-0698>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit 1st response

Connection Style:

Plain (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

150.0 pounds per square inch 1st response 300.0 pounds per square inch 2nd response

Thread Size:

2.000 inches all ends

Material:

Copper alloy body

Material Specification:

Qq-n-286 federal specification 1st material response stem or b164-61 federal specification 2nd material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight thru

Test Data Document:

03950-acid 882057057 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0