## NSN 4820-00-483-8191

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-483-8191

| Pipe Size Accommodated:   |
|---|
| 0.250 inches 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Flow Control Device:  |
| Poppet  |
| Disk Loading Method:  |
| Spring  |
| Maximum Operating Temp:   |
| 250.0 degrees fahrenheit single response                                  |
| Connection Style:   |
| Plain, optional en (pipe) 1st end   |
| Valve Operation Method:   |
| Automatic   |
| Connection Type:  |
| Threaded internal pipe 1st end  |
| Features Provided:  |
| Pressure tight outlet side  |
| Thready Qty Per Inch (tpi):   |
| 18 1st end  |
| Maximum Operating Pressure:   |
| 2500.0 pounds per square inch single response                             |
| Thread Size:  |
| 0.250 inches 2nd end  |
| Opening Pressure Setting:   |
| 1500.0 pounds per square inch   |
| Material:   |
| Copper alloy  |
| Media For Which Designed:   |
| Hydraulic fluid, mineral base single response                             |
| Style Designator:   |
| Straight through note: to be used for valve bodies of separable sections. |
| Thread Series Designator:   |
| Npt 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A046b0