## NSN 4820-00-489-8218



<b>NSN 4820-00-489-8218</b> Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-489-8218
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Stainless steel flow control device
Material Specification:
Qq-a-250/4, alloy 2024 federal specification single material response seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf 2nd end

## NSN 4820-00-489-8218

Check Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

## Mil-std (military Standard):

Mil-a-8625 spec.

