

View Online at <https://aerobasegroup.com/nsn/4820-00-491-6795>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Pressure seal, ring type

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

775.0 degrees fahrenheit single response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

3.000 inches

**Maximum Operating Pressure:**

600.0 pounds per square inch single response

**Outside Diameter:**

8.250 inches all ends

**Thickness:**

1.250 inches all ends

**First Connection Face To Centerline Distance:**

7.000 inches

**Bolt Hole Diameter:**

0.875 inches all ends

**Second Connection Face To Centerline Distance:**

7.000 inches

**Bolt Circle Diameter:**

6.625 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.250 inches all ends

**Raised Face Diameter:**

5.000 inches all ends

**Material:**

Stainless steel stem

**Material Specification:**

Astma105, grade2 assn standard single material response body

**Media For Which Designed:**

Steam single response

**Style Designator:**

Angle flanged ends

**Specification Or Standard:**

D composition

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0