## NSN 4820-00-493-4342

Restrictor Check Valve - Page 1 of 2

Unf all ends Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/4820-00-493-4342 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Facility:** Bulkhead **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 12.0 degrees all ends Material: Steel comp 303 flow control device **Material Specification:** Qq-s-764, type 303-cancelled federal specification single material response flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize and enamel **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** 

## NSN 4820-00-493-4342

Restrictor Check Valve - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.