# NSN 4820-00-494-1332

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-494-1332

| Thread | Class  |
|--------|--------|
| Thread | Class: |

3a 1st end

**Thread Direction:** 

Right-hand 1st end

# Flow Control Device:

Poppet

# **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

300.0 degrees fahrenheit single response

#### **Connection Style:**

Flared (tube) 1st end

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external tube 1st end

**Mounting Position:** 

Horizontal

#### Maximum Operating Pressure:

4000.0 pounds per square inch single response

# Thread Size:

0.562 inches 2nd end

## Seat Angle:

37.0 degrees 1st end

#### **Outside Diameter Tube Accommodated:**

0.375 inches 2nd end

## Material:

Steel comp 630 flow control device

#### Material Specification:

Qq-a-225/6, alloy 2024 federal specification single material response seat

#### Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Straight thru

# **Thread Series Designator:**

Unf 2nd end

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 4820-00-494-1332

Check Valve - Page 2 of 2

Fiig: A530b0

