NSN 4820-00-494-8106

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-494-8106

View Online at https://aerobasegroup.com/nsn/4820-00-494-8106
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
16 1st end
Adjustable Pressure Range:
+800.0/+1500.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
1000.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Material:
Steel comp 303 flow control device and steel comp 416 flow control device
Surface Treatment:
Passivate
Style Designator:
Angle
Thread Series Designator:
Linif 1 at and

Unjf 1st end

NSN 4820-00-494-8106

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

