## NSN 4820-00-494-8106

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-494-8106 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring Renewable Seat Ring Type: Pressed-in **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end Thready Qty Per Inch (tpi): 16 1st end **Adjustable Pressure Range:** +800.0/+1500.0 pounds per square inch **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 1000.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Steel comp 303 flow control device and steel comp 416 flow control device **Surface Treatment:** 

Passivate

Style Designator:

Angle

Thread Series Designator:

Unjf 1st end

## NSN 4820-00-494-8106

Safety Relief Valve - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0