NSN 4820-00-495-6263

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-495-6263

| View Online at https://aerobasegroup.com/nsn/482 | 0-0 |
|--|-----|
| Thread Direction: | |
| Right-hand all ends | |
| Flow Control Device: | |
| Disk | |
| Bonnet Type: | |
| Inside screw | |
| Bonnet Attachment Method: | |
| Threaded | |
| Renewable Seat Ring Type: | |
| Welded | |
| Maximum Operating Temp: | |
| 250.0 degrees fahrenheit single response | |
| Connection Style: | |
| Plain (pipe) all ends | |
| Valve Operation Method: | |
| Manual | |
| Connection Type: | |
| Threaded external pipe all ends | |
| Features Provided: | |
| Bonnet packing | |
| Maximum Operating Pressure: | |
| 375.0 pounds per square inch single response | |
| Thread Size: | |
| 1.500 inches all ends | |
| Material: | |
| Nickel alloy flow control device | |
| Media For Which Designed: | |
| Water-oil-gas single response | |
| Style Designator: | |
| Straight thru | |
| Thread Series Designator: | |
| Npt all ends | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A046b0 | |
| | |