NSN 4820-00-495-6950

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-495-6950 **Thread Class:** 2a 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 2nd end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 2nd end **Special Features:** Restricted flow at 1500 psi differentiating pressure and mil-h-5606 fluid at 90 degrees f porm 10 degrees f Material: Stainless steel Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Passivate and paint **Style Designator:** Straight thru **Thread Series Designator:** Npt 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-00-495-6950

Restrictor Check Valve - Page 2 of 2



Fiig:

A530b0